



PRODUCT DATA SHEET

NOPEEL™ FLOW ADDITIVE PTI ADDITIVES

DESCRIPTION

PTI NoPeel™ additive is formulated to help epoxy and polyurethane topcoats flow to their maximum ability. This additive keeps the coating from “Orange Peel” and other surface defects that may occur due to surface tension.

COATING PROPERTIES & CHARACTERISTICS

Flash Point	80°F
Weight (lbs per gallon)	6.92 lbs
Color	Clear
Volatile Organic Compounds (VOC)	895 g/l
Specifications	Proprietary

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

MIXING INSTRUCTIONS

Add a 4 oz. bottle to 1 gallon of component A (paint) material only. **DO NOT** add to Comp B (catalyst) material. This is approximately a 4% by volume addition.

If material still does not flow properly, another 4 oz. bottle may be added. **DO NOT** add more than 8 total ounces of additive as it may adversely affect the quality of the cured topcoat.

Must be mixed in **THOROUGHLY** by hand, mechanical mixer, or can be put on a shaker for a minimum of 5 – 10 seconds.

Always refer to the MSDS for all health and safety precautions of this material.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.